This Page Is Inserted by IFW Operations and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents will not correct images, please do not report the images to the Image Problem Mailbox.



PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6:
A61B 17/04

A1 (11) International Publication Number: WO 97/13465

(43) International Publication Date: 17 April 1997 (17.04.97)

(21) International Application Number: PCT/SE96/01269

(22) International Filing Date: 8 October 1996 (08.10.96)

(30) Priority Data: 9503512-7 9 October 1995 (09.10.95) SE

(71) Applicant (for all designated States except US): MEDSCAND MEDICAL AB [SE/SE]; P.O. Box 20047, S-200 74 Malmö (SE).

(72) Inventor; and
(75) Inventor/Applicant (for US only): ULMSTEN, Ulf [SE/SE];
Ridvägen 18 D, S-182 35 Danderyd (SE).

(74) Agents: STRÖM, Tore et al.; Ström & Gulliksson AB, P.O. Box 4188, S-203 13 Malmö (SE).

(81) Designated States: AU, CA, CN, JP, US, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).

Published


With international search report.

Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

(54) Title: SURGICAL INSTRUMENT FOR TREATING FEMALE URINARY INCONTINENCE

(57) Abstract

A surgical instrument for treating female urinary incontinence comprises a shank (10) having a handle (11) at one end thereof, and two curved needle-like elements (21A, 21B) which can be connected one at the time with the shank at the other end thereof to form a curved end portion of the shank and are attached at one end thereof each with one end of a netting (26) which is intended to be implanted into the body and is covered by a thin plastic sheath (34).



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

| AM | Armenia | GB | United Kingdom | MW | Malawi |
|-----|--------------------------|----|------------------------------|----|--------------------------|
| AT | Austria | GE | Georgia | MX | Mexico |
| AU | Australia | GN | Guinea | NE | Niger |
| BB | Barbados | GR | Greece | NL | Netherlands |
| BE | Belgium | HU | Hungary | NO | Norway |
| BF | Burkina Faso | 12 | Ireland | NZ | New Zealand |
| BG | Bulgaria | IT | Italy | PL | Poland |
| B.J | Benin | JP | Japan | PT | Portugal |
| BR | Brazil | KE | Kenya | RO | Romania |
| BY | Belarus | KG | Kyrgystan | RU | Russian Federation |
| CA | Canada | KP | Democratic People's Republic | SD | Sudan |
| CF | Central African Republic | | of Kores | SE | Sweden |
| CG | Congo | KR | Republic of Korea | SG | Singapore |
| CH | Switzerland | KZ | Kazakhstan | SI | Slovenia |
| CI | Côte d'Ivoire | 니 | Liechtenstein | SK | Slovakia |
| CM | Cameroon | LK | Sri Lanka | SN | Senegal |
| CN | China | LR | Liberia | SZ | Sweziland |
| CS | Czechoslovakia | LT | Lithuania | TD | Chad |
| CZ | Czech Republic | LU | Luxembourg | TG | Tago |
| DE | Germany | LV | Latvia | Tj | Tajikistan |
| DK | Denmark | MC | Monaco | TT | Trinidad and Tobago |
| EE | Estonia | MD | Republic of Moldova | UA | Ukraine |
| ES | Spain | MG | Madagascar | UG | Uganda |
| FI | Finland | ML | Mali | US | United States of America |
| FR | France | MN | Mongolia | ĽZ | Uzbekistan |
| GA | Gabon | MR | Mauritania | VN | Viet Nam |

PCT/SE96/01269 WO 97/13465

Surgical instrument for treating female urinary incontinence

5

10

30

35

The invention relates to a surgical instrument for treating female urinary incontinence, of the type described in PCT/SE95/00964 the content of which is incorporated herein by reference, comprising a shank having a handle at one end thereof, and two curved needle-like elements which are each attached at one end thereof to one end of a tape to be implanted into the body, and are constructed to be connected one at the time with the shank to form a curved portion at the other end thereof each element being intended to be passed into the body via the anterior (suburethral) vaginal wall and being dimensioned to extend from the inside surface of the vaginal wall over the back of the pubic bone to the outside of the abdominal wall.

The object of the invention is to further improve the surgical instrument disclosed in said document and for this purpose the instrument of the invention has obtained the characterizing features of claim 1.

The invention will be explained in more detail with reference to the accompanying drawings which disclose the surgical instrument according to the invention and wherein.

FIG. 1 is a side view of the surgical instrument according to the invention,

FIG. 2 is a plan view of the surgical instrument, FIG. 3 is an exploded side view of one of the needles and tape and shrinkage hose to be connected with said needle,

FIG. 4 is a side view of the needle in FIG. 3 with the tape connected therewith,

FIG. 5 is an enlarged fragmentary axial cross sectional view of a coupling of the instrument for connecting an exchangeable needle thereof, and

FIG 6 is a side view of two needles and a tape interconnecting said needles.

In the following description the same reference numerals have been used as in PCT/SE85/00964 for corresponding details of the instrument.

The surgical instrument comprises a cylindrical tubular shank 10 having at one end thereof a handle 11. At the other end of the shank there is a socket 14. A cylindrical shaft 15 is rotatably mounted in the shank and can be rotated manually by means of a knob 16 mounted to one end of the shaft. The other end of the shaft forms a cylindrical portion 17, FIG 5, of smaller outside diameter than the shaft, which joins a portion 18 having external threads, a smooth end portion 19 of further reduced dia-15 meter joining the threaded portion 18, end portion 19 forming a guide pin at said other end of the shaft. Portions 18 and 19 are received in the portion of socket 14 projecting from the shank. The surgical instrument as described so far is in agreement with the instrument disclosed in PCT/SE95/00964 except that the end portion 14' of socket 14 is flattened from opposite sides (cfr FIGS 1 and 2), so that the cross section of said end portion is noncircular.

The surgical instrument also includes an exchangeable and disposable needle 21 which at one end thereof is attached to the shank at one end of the needle and extends over substantially a quarter of a circle to the other, free end thereof in order to follow substantially the profile of the pubis between the vagina and the abdominal wall. The needle has uniform circular cross section and has a smooth, preferably polished outside surface. At the free end thereof the needle forms a point 22 by being terminated by a conical portion.

For attachment of needle 21 to shank 10 the needle forms at said one end thereof a straight portion 30 which

is cylindrical but has milled flat faces 31 over that part of said portion 30, extending from the adjacent end of the needle, which shall be received by socket portion 14'. The needle should be oriented in a predetermined rotational 5 position in relation to the shank, and more particularly it should project at right angles to the plane of handle 11. This rotational position is secured by the non-circular shape of socket portion 14' and the end portion of the needle having the flat faces 31, which fits into socket portion 14'. The end portion of the needle having the flat faces 31 joins the body of the needle over e conical portion 32, which tapers towards a shoulder 33.

An axial blind hole extends from the end surface of the needle said hole having a threaded portion 23 and inwardly thereof a narrower, cylindrical portion 24. Guide pin 19 is dimensioned to be guidingly received by said latter portion when the threaded portion 18 for attaching needle 21 to the rest of the surgical instrument is screwed into threaded portion 23 of the blind hole by rotating shaft 15 by manual rotation of knob 16, the end surfaces of the shank and the needle being pressed against each other. Also this attachment is in agreement with that described in PCT/SE95/00964.

When the method as described in PCT/SE95/00964 is practised two needles 21A and 21B, FIG. 6 of the embodiment described shall be connected one at each end of a tape 26. According to the present invention the tape of the preferred embodiment comprises a mesh or netting forming openings of the order of 1 mm. A suitable material for the tape is PROLENE®, a knitted polypropylene mesh having a thickness of 0,7 mm manufactured by Ethicon, Inc., Sommerville, New Jersey, USA. This material is approved by FDA in USA for implantation into the human body. The netting (tape) preferably has a width of approximately 10 mm and is enclosed in a thin polyethylene sheath 34 which in 35

WO 97/13465 PCT/SE96/01269

flattened condition has substantially the same width as the tape although a difference in width is shown in FIG 2 in order to make the provision of the sheath more clear. The length of the netting should be approximately 400 mm. The netting and the sheath are interconnected by means of two rows 35 of stiching. The end portion of the sheath is attached to the conical portion 32 of the needle by means of a suitable strong glue, and the interconnection of the needle and sheath is covered by a shrink hose 36 of rubber which extends from the shoulder 33 over the conical portion 32 and partly over the cylindrical end portion 30 of the needle. The shrink hose is substantially flush with the surface of the needle at the shoulder. By this arrangement the netting is securely attached to the needle.

The purpose of sheath 34 is above all to facilitate the insertion of the netting in the manner described in PCT/SE95/00964 i e when the netting is pulled at the ends thereof from the vaginal wall to the abdominal skin and to avoid that rough edges of the netting irritate or damage the body tissues.

15

20

30

35

When the tape has been positioned in the correct position as a sling around the urethra the polyethylene sheath shall be removed, and in order to facilitate the removal the sheath should be perforated at the longitudinal center thereof as indicated by a dot-and-dash line 37 in FIG. 6, so that the two halves of the sheath can be withdrawn from the body by pulling at the respective outer ends thereof the halves being separated at the perforation under the influence of the pulling force.

The purpose of the polyethylene sheath is also to protect the netting during attachment to the needles and during handling before and during insertion into the body.

The longitudinal center of the tape and sheath should be indicated by a visible colour mark 38, FIG. 6 so that the surgeon readily can see when the netting is sym-

WO 97/13465 PCT/SE96/01269

metrically located with reference to urethra during the surgery.

15

25

CLAIMS


- 1. Surgical instrument for treating female urinary incontinence, comprising a shank (10) having a handle (11) at one end thereof, and two curved needle-like elements (21) which are each attached at one end thereof to one end of a tape (26) to be implanted into the body, and are constructed to be connected one at the time with the shank to form a curved portion at the other end end thereof each element being intended to be passed into the body via the anterior (suburethral) vaginal wall and being dimensioned to extend from the inside surface of the vaginal wall over the back of the pubic bone to the outside of the abdominal wall, c h a r a c t e r i z e d in that the tape comprises a netting (26) enclosed by a thin plastic sheath (34).
 - 2. Instrument as in claim 1 c h a r a c t e r i z e d in that the netting (26) is made of polypropylene.
 - 3. Instrument as in claim 2 c h a r a c t e r i z e d in that the sheath (34) is made of polyethylene.
- 4. Instrument as in any of claims 1 to 3
 20 characterized in that the sheath (34) is perforated at the longitudinal center thereof.
 - 5. Instrument as in any of claims 1 to 4 c h a r a c t e r i z e d in that the netting (26) and the sheath are interconnected by stitching ((35)).
 - 6. Instrument as in any of claims 1 to 5 c h a r a c t e r i z e d in that the needle-like element (21) comprises a non-circular end portion fitting into a non-circular socket (14') at said other end of the shank (10).
- 7. Instrument as in claim 6
 c h a r a r a c t e r i z e d in that said end portion of
 the needle-like element (21) joins the rest of the element
 by a conical portion (32) tapering towards a shoulder (33)
 on the needle-like element.

20


- 8. Instrument as in claim 7 c h a r a c t e r i z e d in that the netting (26) and the sheath (34) are connected to the needle-like element (21) by gluing to said conical portion (32).
- 9. Instrument as in claim 8 c h a r a c t e r i z e d in that the netting (26) and the sheath (34) at the site of attachement thereof are covered by a shrink hose (36).
- 10. Instrument as in claim 9 c h a r a c t e r i z

 10 e d in that one end of the shrink hose (36) abuts the shoulder (33) and is substantially flush with the surface of the needle-like element at said shoulder.
- 11. Instrument as in claim 9 or 11, characterized in that the netting (26) and the sheath (34) project from the shrink hose (36) at the other end thereof.
 - 12. Instrument as in any of claims 1 to 11, c h a r a c t e r i z e d in that a visable marking (38) is provided on the sheath (34) at the longitudinal center thereof.


WO 97/13465





SUBSTITUTE SHEET




SUBSTITUTE SHEET







SUBSTITUTE SHEET



SUBSTITUTE SHEET

INTERNATIONAL SEARCH REPORT

International application No. PCT/SE 96/01269

| A. CLAS | SIFICATION OF SUBJECT MATTER | | | | | | | | |
|--|---|--|-----------------------------|--|--|--|--|--|--|
| IPC6: A61B 17/04 According to International Patent Classification (IPC) or to both national classification and IPC | | | | | | | | | |
| B. FIELDS SEARCHED | | | | | | | | | |
| Minimum d | ocumentation searched (classification system followed b | y classification symbols) | | | | | | | |
| IPC6: | A61B | | | | | | | | |
| Documenta | tion searched other than minimum documentation to the | * | the fields searched | | | | | | |
| | FI,NO classes as above | The state of the s | | | | | | | |
| Electronic d | ata base consulted during the international search (name | of data base and, where practicable, search | terms used) | | | | | | |
| | | | • | | | | | | |
| | | | | | | | | | |
| C. DOCUMENT'S CONSIDERED TO BE RELEVANT | | | | | | | | | |
| Category* | Citation of document, with indication, where ap | propriate, of the relevant passages | Relevant to claim No. | | | | | | |
| P | SE 503271 C2 (MEDSCAND AB), 29 / (29.04.96) | April 1996 | | | | | | | |
| | | | | | | | | | |
| A | WO 9003766 A1 (P.E. PETROS), 19 April 1990 (19.04.90) | | | | | | | | |
| | (13.04.30) | | | | | | | | |
| | | | | | | | | | |
| A | DE 4334419 A1 (KLINIKUM DER ALBERT-LUDWIGS-UNIVERSITÄT (13 April 1995 (13.04.95) | FREIBURG.), | | | | | | | |
| | | | | | | | | | |
| A | US 5403328 A (SHALLMAN,R.W.), 4 April 1995 | | | | | | | | |
| | (04.04.95) | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| Further documents are listed in the continuation of Box C. See patent family annex. | | | | | | | | | |
| * Special categories of cited documents: "A" document defining the general state of the art which is not considered the principle or theory underlying the invention. | | | | | | | | | |
| | particular relevance scurrent but published on or after the international filing date. | "X" document of particular relevance: the | claimed invention cannot be | | | | | | |
| | nt which may throw doubts on priority claim(s) or which is establish the publication date of another establin or other | considered novel or cannot be considered novel or cannot be considered along the document is taken along | | | | | | | |
| "Y" document of particular relevance: the claimed invention ca "O" document referring to an oral disclosure, use, exhibition or other considered to involve an inventive step when the document | | | | | | | | | |
| | nt published prior to the international filing date but later than rity date claimed | heing obvious to a person stilled in the document member of the same patent | c art | | | | | | |
| Date of the actual completion of the international search Date of mailing of the international search report | | | | | | | | | |
| 06.03.97 | | | | | | | | | |
| 5 March | mailing address of the ISA | Authorized officer | | | | | | | |
| Swedish Patent Office | | | | | | | | | |
| | S-102 42 STOCKHOLM No. + 46 8 666 02 86 | Anette Hall Telephone No. + 46 8 782 25 00 | | | | | | | |

INTERNATIONAL SEARCH REPORT

Information on patent family members

03/02/97

International application No.

PCT/SE 96/01269

| Patent document cited in search report | | Publication date | Patent family member(s) | | Publication date | |
|--|---------|------------------|---|--|--|--|
| E-C2- | 503271 | 29/04/96 | AU-A- SE-A- WO-A- | E-A- 9402872 01 | 22/03/96 01/03/96 07/03/96 | |
| 60-A1- | 9003766 | 19/04/90 | AT-T- AU-A- DE-D,T- EP-A,B- SE-T3- US-A- | 119758 4406489 68921762 0437481 0437481 5112344 | 15/04/95 01/05/90 03/08/95 24/07/91 12/05/92 | |
| DE-A1- | 4334419 | 13/04/95 | NONE | | | |
| JS-A- | 5403328 | 04/04/95 | CA-A- EP-A- | 2094685 0567130 | 23/10/93 27/10/93 | |